## Whirlamatic™ 17 & 20 UHS

Burnishers



### FACT SHEET



For superior performance, durability and simple operation, depend on the Whirlamatic™ 17 or 20 UHS. These 17 and 20 inch (43 & 51 cm) cordelectric burnishers give floors a mirror-like shine in one pass. Incorporated into both are performance features that ensure maximum productivity. An exclusive Constant-Flo™ design uses a patented torsion spring design to eliminate any operational variances and the need for caster wheels, making burnishing almost foolproof. Neither uneven floors nor operator inexperience can affect the brush/pad pressure. Weight is evenly maintained while brush/pad turns at 1500 rpm's. The result is a consistent luster across the floor.

Simplicity in design reduces downtime. Direct drive to the brush and pad holder eliminates the need for belts and pulleys. With the convenience of cord-electric operation, the 17 or 20 UHS is ready when you are. Their size and low profile make them maneuverable in obstructed areas. The 20 UHS burnishes at a rate of 10,000 sq ft (925 m²) an hour; 9,100 sq ft (840 m²) for the 17 UHS.

Operation is simple and safe because they move along without side-to-side torque. Large, non-marking wheels make them easy to transport.

#### TYPICAL APPLICATIONS INCLUDE

- Schools and Universities
- Healthcare Facilities
- Supermarkets
- Retail Outlets
- Institutions
- Contract Cleaners

### **OPTIONAL ACCESSORIES INCLUDE**

- Burnishing Brushes
- Pads



# Advance Whirlamatic™ 17 & 20 UHS

### **Burnishers**



Non-tiring twist-grip start stops automatically when the operator lets go. Safety interlock button prevents accidental start.



Both models tip back to rest on a second set of big fourinch (10 cm) wheels for easy transportation.



Permanent brush/pad holder mounted directly to motor. Eliminates transmission problems. Pad attaches easily to center mounting hub.



Low profile housing lets the machine under obstructions. Non-marking rubber bumper provides protects machine.



## Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your products by factory-trained personnel around the world, as well as fast parts delivery.
- Maintain peak performance with genuine APA parts.



## Comes in 17 in or 20 in (43 or 51 cm) pad sizes

# **Technical Specifications**

Motor 17 UHS — 20 UHS — (1.5 hp, 100V/50	1.5 hp, 115v/60 Hz, rectified DC 1.5 hp, 115v/60 Hz, rectified DC, -60 or 230V/50 Hz models available)	<b>Dimensions</b> Width  Length	17 UHS – 18 in (45 cm) 20 UHS – 21 in (53 cm) 17 UHS – 21½ in (55 cm)
Brush or Pad Holders	Permanently attached 17 in (43 cm) or 20 in (51 cm) burnishing brush. Permanently attached 17 in (43 cm) or 20 in (51 cm) pad holder.	Height  Net Weight	20 UHS – 24 in (61 cm) 17 UHS – 47 in (119 cm) w/handle 20 UHS – 47 in (119 cm) w/handle
Pad Speed	1,500 rpm		82 lb (37 kg) with brush
Wheels	Four 4 in (10 cm) operating and transport wheels made of non-marking rubber.	20 UHS Net —	80 lb (36 kg) with pad holder 85 lb (38.5 kg) with brush 83 lb (38 kg) with pad holder
Transmission Cable Length	Direct-drive from motor shaft. 75 ft (23 m)	<b>Ship Weight</b> 17 UHS —	105 lb (47 kg) with brush 103 lb (46 kg) with pad holder
Construction	Cast aluminum skirt housing, malleable iron and pentagonal steel	20 UHS —	108 lb (49 kg) with brush 106 lb (48 kg) with pad holder
	handle with baked-on powder paint finish. Non-marking bumper surrounds housing. ABS motor housing and cover.	Part Number 17 UHS — 20 UHS —	56 183 100 56 183 700

Specifications are subject to change without notice.





14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com

Phone: 800-850-5559 Fax: 800-989-6566 396 Watline Avenue

Mississauga, Ontario, Canada L4Z 1X2 www.nilfisk-advance.com

Phone: 800-668-8400 or 905-712-3260 Fax: 800-263-5111 or 905-712-3255